



**Specifications 技术规格:**

Current Rating: 3A  
 额定电流: 3A  
 Insulation Resistance: 1000 MW Min.  
 绝缘电阻: 最小1000M $\Omega$   
 Dielectric Withstanding: 800V AC  
 耐电压: 800V AC  
 Contact Resistance: 20m Max.  
 接触电阻: 最大20m $\Omega$   
 Operating Temperature: -25° C to +85° C  
 工作温度: -25° C 到 85° C

**Materials/材料:**

Contact Material: Phosphor Bronze (Tin plated)  
 接触端子材料: 磷铜 (镀锡)  
 Recommended wire gauge: AWG28#-24#  
 推荐线规: AWG28#-24#

 浙江快利电子有限公司  
 Zhejiang Kuaili Electronic Co., Ltd

REV. A UNIT. MM SCALE. --- 

GENERAL TOLERANCE	
X.* $\pm 3'$	X. $\pm 0.35$
.X* $\pm 2'$	.X $\pm 0.25$
.XX* $\pm 1'$	.XX $\pm 0.15$
.XXX* $\pm 0.5'$	.XXX $\pm 0.10$

DESIGN:	李晓明	DATE:	16'.4.20
CHECKED:	李晓明	DATE:	16'.4.20
AUDITED:	张宁	DATE:	16'.4.20
APPROVED:	朱建华	DATE:	16'.4.20

DWG. NO.	
PART NO.	KL-PHC-TE-2824

TITLE.	PHC-TE
--------	--------